



SAFETY DATA SHEET

Huemiller Wood Stain and Sealant

1. PRODUCT AND COMPANY IDENTIFICATION

DATE ISSUED:	1/24/2019
SDS REF. No:	

PRODUCT NAME: Huemiller Wood Stain and Sealant

PRODUCT CODE: 1210-BR-93, 1210-BR-94, 1210-BR-95, 1210-BR-96, 1210-BR-97, 1210-BR-98.

SYNONYMS:

CAS NUMBER:

PRODUCT USE: Paint

MANUFACTURER:

CIC Coatings, LLC
2935 Almeta Ln

McKinney, TX,
877-258-8797

24 HR. EMERGENCY TELEPHONE NUMBER

ChemTel : (800)255-3924

2. HAZARDS IDENTIFICATION

GHS Classification:

Skin irritation
Eye irritation
Aspiration hazard

Category 2
Category 2A
Category 1

Hazard Symbols:



Single word: Warning

Hazard statements:

Combustible liquid.
Harmful if swallowed, in contact with skin or if inhaled
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.



SAFETY DATA SHEET

Huemiller Wood Stain and Sealant

Precautionary statements:

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ eye protection/ face protection.

Response:

IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.

IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or doctor/ physician if you feel unwell.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention.

Take off contaminated clothing and wash before reuse.

In case of fire: Use dry sand, dry chemical or alcohol resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards:

None Known.



SAFETY DATA SHEET

Huemiller Wood Stain and Sealant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Concentration (% wt)
Distillates, hydrotreated heavy paraffinic	64742-54-7	70-90%
Mineral Spirits	64742-47-8	10-20%

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. FIRST AID MEASURES

If inhaled:

Remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get immediate medical advice/ attention.

In case of skin contact:

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Get immediate medical advice/ attention.
Wash contaminated clothing before reuse.

In case of eye contact:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
Get medical advice/ attention.

If swallowed:

Seek medical advice.

Most important symptoms and effects, both acute and delayed:

Irritating to eyes, respiratory system and skin.
Harmful if swallowed, in contact with skin or if inhaled Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.

Notes to physician:

Treat symptomatically.



SAFETY DATA SHEET

Huemiller Wood Stain and Sealant

5. FIRE FIGHTING MEASURES

Suitable extinguishing media:	Water spray, Dry chemical, Carbon dioxide (CO ₂)
Unsuitable extinguishing media:	None known.
Specific hazards during firefighting:	Forms peroxides of unknown stability.
Hazardous combustion products:	No hazardous combustion products are known
Further information:	Combustible liquid and vapour.
Special protective equipment for firefighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:	Wear appropriate personal protective equipment.
Environmental precautions:	Avoid release to the environment.
Methods and materials for containment and cleaning up:	Prevent runoff from entering drains, sewers, or streams.
Notification Procedures:	According to local laws a regulations.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: Avoid breathing mist or vapors. Avoid contact with eyes, skin, and clothing. Use only with adequate ventilation. Wash thoroughly after handling.

CONDITIONS FOR SAFE STORAGE, INCLUDING INCOMPATIBILITIES : KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.



SAFETY DATA SHEET

Huemiller Wood Stain and Sealant

8. EXPOSURE CONTROLS\PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates, hydrotreated heavy paraffinic	64742-54-7	TWA	5 mg/m ³	ACGIH
		TWA	5 mg/m ³	NIOSH REL
		TWA	5 mg/m ³	OSHA Z-1
		TWA	5 mg/m ³	OSHA P0
Mineral Spirits	64742-47-8	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m ³	NIOSH REL
		TWA	50 ppm 240 mg/m ³	OSHA Z-1
		TWA	25 ppm 120 mg/m ³	OSHA P0

ENGINEERING CONTROLS: Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

SKIN: Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.



SAFETY DATA SHEET

Huemiller Wood Stain and Sealant

RESPIRATORY: If exposure may or does exceed occupational exposure limits (Section 8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134, use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors

WORK HYGIENIC PRACTICES: Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

COMMENTS: May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

COLOR: Pigmented

ODOR: Faint aliphatic odor

pH: n/a

BOILING POINT: 171 C

FREEZING POINT: -75 C

FLASH POINT: 135 F (closed cup)

VOLATILE ORGANIC COMPOUNDS: 147 G/L

(VOC Theoretical – As Packaged)

HAZARDOUS AIR POLLUTANTS (HAP's): NONE

(HAP's Theoretical – As Packaged)

SOLUBILITY IN WATER: n/a

DENSITY (Lb/Gal): 7.188

EVAPORATION RATE: No further relevant information available

SPECIFIC GRAVITY: .836



SAFETY DATA SHEET

Huemiller Wood Stain and Sealant

10. STABILITY AND REACTIVITY

STABILITY: Yes

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Avoid Freezing

POLYMERIZATION : Avoid heat, flame, and other sources of ignition.

HAZARDOUS DECOMPOSITION PRODUCTS: None known

INCOMPATIBLE MATERIALS: Strong Oxidizing agents

POSSIBILITY OF HAZARDOUS REACTIONS : No Data Available

11. TOXICOLOGICAL INFORMATION

Acute Toxicity Estimate: Not Determined

Acute effects:

EYE: Causes Serious Eye Irritation

SKIN: Causes skin irritation. Allergic reactions are possible.

INHALATION: Harmful if inhaled. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs.

INGESTION: Harmful if swallowed.

CHRONIC TOXICITY:

Carcinogenicity: Not classified based on available information.

Reproductive toxicity: no adverse effect observed.

Specific Target Organ toxicity-single exposure: not classified



SAFETY DATA SHEET

Huemiller Wood Stain and Sealant

Specific Target Organ toxicity-repeated exposure: not classified

12. ECOLOGICAL INFORMATION

ECOTOXICITY :

This product may be harmful or fatal to plant and animal life if released into environment. This material is not expected to be harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

MOBILITY:

No data available.

PERSISTENCE AND DEGRADABILITY:

This material is not expected to be readily biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

POTENTIAL TO BIOACCUMULATE:

Bioconcentration Factor: No data available. Octanol/Water Partition Coefficient: No data available

13. DISPOSAL CONSIDERATIONS

RECOMMENDATIONS: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

SAFE HANDLING: Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

	DOT	IMDG	IATA
UN Number	Not regulated	Not regulated	Not regulated
Proper shipping Name	Not relevant	Not relevant	Not relevant
Hazard Class	N/A	N/A	N/A
Packing Group	N/A	N/A	N/A
Marine Pollutant	NO	NO	NO

***** CIC Coatings, LLC verifies that the material was supplied and shipped in the proper packages in accordance with DOT and federal regulations that are applicable to the mode of transportation**



SAFETY DATA SHEET

Huemiller Wood Stain and Sealant

selected. The shipper must verify that the packaging supplied is acceptable to be re-shipped in per the federal regulations applicable to the mode of transportation for reshipment. Regulations may change depending on mode of transportation selected.***

15. REGULATORY INFORMATION

EPA REGULATION SARA SECTION 311/312 HAZARDS: None Known

All components of this product are on the TSCA list. This material contains no known products restricted under SARA Title III, Section 313 in amounts greater or equal to 1%.

REGULATORY LISTS SEARCHED:

- 01-1=IARC Group 1
- 03=EPCRA 313
- 01-2A=IARC Group 2A
- 04=CA Proposition 65
- 01-2B=IARC Group 2B
- 05=MA RTK 02=NTP Carcinogen
- 06=NJ RTK 07=PA RTK

No components of this material were found on the regulatory lists above.


CHEMICAL INVENTORIES: All components comply with the following chemical inventory requirements: AICS (Australia), DSL (Canada), EINECS (European Union), ENCS (Japan), IECSC (China), KECI (Korea), PICCS (Philippines), TSCA (United States).

NEW JERSEY RTK CLASSIFICATION: Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows: PETROLEUM OIL

16. OTHER INFORMATION

HMIS RATING	
Health :	2
Flammability :	1
Reactivity :	0
Personal Protection :	I

NFPA CODES



REVISION INDICATOR : No Data Available

MANUFACTURER DISCLAIMER: To the best of CIC Coatings, LLC knowledge, all information, recommendations, and suggestions appearing herein concerning this product are taken from raw material sources or based upon data believed to be reliable. Although reasonable are has b

Legend

ACGIH: American Conference of Governmental Industrial Hygienists
CAS No.: Chemical Abstract Service Registry Number
CERCLA: Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)
CPR: Controlled Product Regulations (Canada)
DOT: Department of Transportation (U.S.)
EPA: Environmental Protection Agency (U.S.)
GHS: Globally Harmonized System of Classification and Labeling of Chemicals
HEPA: High-Efficiency Particulate Air
HMIS: Hazardous Materials Identification System
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association
IMDG: International Maritime Dangerous Goods code
LPP: Limité Permissible Ponderado (Chile)
NIOSH: National Institute of Occupational Safety and Health (U.S.)
NFPA: National Fire Protection Association (US)
NTP: National Toxicology Program (US)
OSHA: Occupational Safety and Health Administration (U.S.)
PEL: Permissible Exposure Limit
SARA: Superfund Amendments and Reauthorization Act (U.S. EPA)
SDS: Safety Data Sheet
STEL: Short Term Exposure Limit (15 minute Time Weighted Average)
STOT: Specific Target Organ Toxicity (GHS Classification)
TLV: Threshold Limit Value
TSCA: Toxic Substances Control Act (U.S.)
TWA: Time Weighted Average (exposure for 8-hour workday)
U.S.: United States
VOC: Volatile Organic Compounds
WHMIS: Canadian Workplace Hazardous Materials Information System